



## **SOLACE** Dialysis Chair

Adapt to your patient's needs

# Dialysis Chair

## SOLACE



### Structure

Epoxy-coated steel tube frame.

Scissor-lift system provides optimum stability and supports weights of up to 230 kg.

Integrated portering handle for ease of transport

### Comfort

100% usable patient surface.

Sections fully adjustable with medical grade electric motors compliant with EN 60601-1.

Handset controls independent electric adjustment of height, backrest, legs and Trendelenburg position

Contoured polyurethane armrests fully adjustable for patient comfort.

### Upholstery

High-density polyurethane foam for optimum patient comfort. 10 cm of height.

Upholstered with high quality anti-microbial, abrasion-resistant, Crib 5 vinyl. Easy to clean and maintain.

### Ease Of Handling

Handset designed to allow quick and easy positioning of the chair sections.

Includes two pre-programmed functions: emergency Trendelenburg (shock position) and patient exit position (height descends to minimum, backrest and legrest achieve chair position).

Four Ø 125 mm diameter swivel castors with central brake and steer.

Electric adjustment of footrest.

### Safety

Emergency release of backrest for quick lowering of the section in the event of an emergency, battery or power failure.

Low-voltage medical grade electric motors compliant with EN 60601-1.

Conforms to Regulation (EU) 2017/745.

## Specifications

# SOLACE DIALYSIS CHAIR

### Dialysis Chair: SOLACE

External dimension	220 x 87.5 cm
Patient surface	214 x 57 cm
Backrest dimensions	88 x 57 cm
Seat dimensions	54 x 57 cm
Legrest dimensions	72 x 57 cm
Height adjustment	51–76 cm
Backrest tilting	72°
Footrest dimensions	25 x 58 cm
Trendelenburg	25°
Maximum load	230 kg
Weight w/o accessories	98 kg

### Electric features:

Power supply	100-240V 50-60Hz
Maximum consumption	1,6 A
Protection Indicator	IP54
Class of protection	Class II
Surge Protection	Type B



[www.medi-plinth.co.uk](http://www.medi-plinth.co.uk)

7-11 Holywells Road, Ipswich, Suffolk IP3 0DL – Call: +44 (0) 1473 212010